

MAX001S - HDS

175 x 115 x H47 mm
6.88 x 3.22 x H1.61 inch

157 x 82 x H41 mm
6.18 x 3.22 x H1.61 inch

12 + 29 mm
0.47 + 1.14 inch

S : 0,15 kg / 0.33 lb
HDS : 0,16 kg / 0.35 lb


-10 / 80 °C / 14 / 176° F

Capacità / Capacity
0.527 lt



Stampaggio: ad iniezione
Process: Injection molding

Materiale / Materials
POLIPROPILENE/POLYPROPYLENE
NYLON (Serrature / Latches)
POLIURETANO/POLYURETHANE
(Spugna / foam)



VIDEO S & HDS



Shipping & Logistic info

12 pz. per cartone
12 pcs. x carton



2,24 Kg per cartone
4.93 lb gross weight



IP67
RATING

- Guarnizione ermetica / Watertight seal around lid
- Valvola automatica di pressurizzazione / Automatic pressure release valve
- Sistema di impilabilità / Stackable interlocking system
- Resistenza agli urti / Thick body material



SCREEN PRINTING & CUSTOM LABEL
SERIGRAFIA & ETICHETTA CUSTOM



CUSTOMIZED FOAM INLAY
INTERNI IN SPUGNA FUSTELLATA



LASER MARKING OR ENGRAVING
INCISIONE O MARCATURA LASER



CUSTOM COLOUR
COLORI CUSTOM