

MAX002S - HDS

230 x 175 x H53 mm
9.05 x 6.88 x H2.08 inch

212 x 140 x H47 mm
8.34 x 5.51 x H1.85 inch

14 + 33 mm
0.55 + 1.30 inch

S : 0,28 kg / 0.61 lb
HDS : 0,33 kg / 0.72 lb


-10 / 80 °C / 14 / 176° F

Capacità / Capacity
1.39 lt



Stampaggio: ad iniezione
Process: Injection molding

Materiale / Materials
POLIPROPILENE/POLYPROPYLENE
NYLON (Serrature / Latches)
POLIURETANO/POLYURETHANE
(Spugna / foam)



VIDEO S & HDS



Shipping & Logistic info

12 pz. per cartone
12 pcs. x carton



4,00 Kg per cartone
8.81 lb gross weight



IP67
RATING

- Guarnizione ermetica / Watertight seal around lid
- Valvola automatica di pressurizzazione / Automatic pressure release valve
- Sistema di impilabilità / Stackable interlocking system
- Resistenza agli urti / Thick body material



SCREEN PRINTING & CUSTOM LABEL
SERIGRAFIA &
ETICHETTA CUSTOM



CUSTOMIZED FOAM INLAY
INTERNI IN SPUGNA
FUSTELLATA



LASER MARKING OR ENGRAVING
INCISIONE O
MARCATURA LASER



CUSTOM COLOUR
COLORI CUSTOM