

MAX400S - HDS

 456 x 290 x H318 mm
17.95 x 11.41 x H12.51 inch

 400 x 230 x H260 mm
15.74 x 9.05 x H10.23 inch

 47.5 + 212.5 mm
1.87 + 8.36 inch

 S : 2,84 kg / 6.26 lb
HDS : 3,58 kg / 7.89 lb


 -51 / 90 °C / -59.8 / 194° F

 Capacità / Capacity
22 lt



 Stampaggio: ad iniezione
Process: Injection molding

 Materiale / Materials
POLIPROPILENE/POLYPROPYLENE
NYLON (Serrature / Latches)
POLIURETANO/POLYURETHANE
(Spugna / foam)



VIDEO S & HDS



- Guarnizione ermetica / Watertight seal around lid
- Valvola automatica di pressurizzazione
Automatic pressure release valve
- Sistema di impilabilità / Stackable interlocking system
- Resistenza agli urti / Thick body material
- Chiusure di sicurezza a doppio step / Easy to open double throw latches
- Manico morbido ad alta ergonomia / Load tested soft grip handle
- Pareti spesse ANTIURTO / Thick body material
- Punti di fissaggio per varie applicazioni / Extra fixing points
- Cerniera lungo tutto il profilo della valigia / Fully length hinges
- Perni in nylon ANTI corrosione / Nylon pins corrosion free

Shipping & Logistic info

2 pz. per cartone
2 pcs. x carton



6,70 Kg per cartone
14.77 lb gross weight



IP67
RATING

MIL SPECS

DEF STAN 81-41
STANAG 4280
MIL STD 810H

ATA300



SCREEN PRINTING &
CUSTOM LABEL
SERIGRAFIA &
ETICHETTA CUSTOM



CUSTOMIZED
FOAM INLAY
INTERNI IN SPUGNA
FUSTELLATA



LASER MARKING
OR ENGRAVING
INCISIONE O
MARCATURA LASER



CUSTOM COLOUR
COLORI CUSTOM