



TEST REPORT

Customer's name	Panaro s.r.l.	
Address	Via delle Scienze , 313 Vignola (MO) -Italy	
Test item description	Suitcase	
Trademark	PANARO	
Model	MAX1090 H510	
Testing laboratory	Teslab S.r.l.	
Address	Via delle Cateratte, 84 Livorno	
Report reference n°	25A299A	
Written by (name, function and signature)	D. Maenza Laboratory Technician	
Approved by (name, function and signature)	G. Romano Laboratory Manager	
Date of issue	2026-02-09	
All rights reserved. This report shall not be reproduced except in full in any form or by any means, including photocopying or recording, without the written permission of Teslab S.r.l.		
The results contained in this report reflect the results for this particular model and serial number. It is the responsibility of the manufacturer to ensure that all production models meet the intent of the requirements detailed within this report.		

Master Report AMB 2.09

1 APPLICABLE DOCUMENTS

1.1 Reference standards

Reference standard	Title
Acceptance test procedure	Prove STANAG – DEF -STAN 81-41 – MIL – STD 810H Rev.11 2025-09-03
EN 60529:1991+A2:2013 +AC:2016+A2:2013/AC:2019 +EN 60529:1991/corrigendum May 1993	Degrees of protection provided by enclosures (IP Code)

1.2 Other documents

These documents are provided by the customer and used/analyzed to check the conformity to the reference standards.

Document	Title	(n°, edition, date, ...)
MIL-STD 810H	Department of defense test method standard for environmental engineering considerations and laboratory tests	--
STANAG 4280	Nato level of packaging	Edition 2
DEF-STAN 81-41 Part 3	Packaging of defence material	2007

2 SUMMARY OF THE TEST PERFORMED

2.1 Durability and resistance to environmental conditions

Type of test		Equipment under test	Test Result
--	Storage High Temperature Method 501.7 (Procedure I)	EUT-4	COMPLIANT
C	Dry Heat Test (NATO level 1)	EUT-4	COMPLIANT
E – D	Vertical and Horizontal impact test (NATO level 1) – After Dry Heat Test	EUT-4	COMPLIANT
--	Storage Low Temperature Method 502.7 (Procedure I)	EUT-5	COMPLIANT
G	Low Temperature test (NATO level 1)	EUT-5	COMPLIANT
E – D	Vertical and Horizontal impact test (NATO level 1) – After Cold Test	EUT-5	COMPLIANT
--	Shock - Method 516.8 Transit Drop (Procedure IV)	EUT-3	COMPLIANT
E – D	Vertical and Horizontal impact test (NATO level 1)	EUT-3	COMPLIANT
--	Vibration - Method 514.8 General vibration (Procedure I)	EUT-1	COMPLIANT
K	Vibration Test: Sinusoidal (NATO level 1)	EUT-1	COMPLIANT
--	Degrees of protection indicated by first characteristic numeral (IP6X)	EUT-2	COMPLIANT
--	Degrees of protection indicated by second characteristic numeral (IPX7)	EUT-1	COMPLIANT